ALL-NEW

KAULER PRO

ELITE SERIES

EXPERIENCE SUPERIOR PERFORMANCE.

Reach the full potential of your workday with the Hauler PRO Series. With a zero-maintenance ELITE lithium powertrain activated by Samsung SDI battery technology, the Hauler PRO Series has the power to get the job done, all while providing the benefits of zero-maintenance batteries and lower operational costs.



ZERO MAINTENANCE ELITE LITHIUM BATTERY

1500LB / 1200LB TOWING CAPACITY

1200LB / 900LB LOAD CAPACITY

CUSHMAN

12 CU FT CARGO BED





HAULER PRO ELITE

HAULER PRO-X ELITE

ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger

CUSHMAN.COM

©2022 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82309-G1 (Rev. 06/2022)

HAULER PRO / ELITE SERIES

HAULER PRO ELITE

HAULER PRO-X ELITE

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	

DIMENSIONS

	110 :- //	
OVERALL LENGTH	119 in (302 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)	77 in (196 cm)
WHEEL BASE	76.8 in (195 cm)	77.5 in (196.9 cm)
FRONT WHEEL TRACK	35 in (88.9 cm)	38.0 in (96.56 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)	
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m3)	
CARGO BOX DIMENSIONS	39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)	
CARGO BOX MATERIAL	Roto-Molded Polyethylene	

POWER

POWER SOURCE56.7V Li-Ion BatteryMOTOR TYPEAC InductionHORSEPOWER (KW)14.9 HP (11.1 kW)ELECTRICAL SYSTEM48V Primary, 12V AuxiliaryBATTERY (QTY/TYPE)4.2 ELITE - Twin PackBATTERY CHARGER811 Watt World ChargerKEY OR PEDAL STARTPedalDRIVE TRAINMotor Shaft Direct DriveTRANSAXLEDifferential with Helical GearsSPEED CONTROLLER350 Amp AC Controller			
HORSEPOWER (KW) 14.9 HP (11.1 kW) ELECTRICAL SYSTEM 48V Primary, 12V Auxiliary BATTERY (QTY/TYPE) 4.2 ELITE - Twin Pack BATTERY CHARGER 811 Watt World Charger KEY OR PEDAL START Pedal DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Differential with Helical Gears	POWER SOURCE	56.7V Li-Ion Battery	
ELECTRICAL SYSTEM48V Primary, 12V AuxiliaryBATTERY (QTY/TYPE)4.2 ELITE - Twin PackBATTERY CHARGER811 Watt World ChargerKEY OR PEDAL STARTPedalDRIVE TRAINMotor Shaft Direct DriveTRANSAXLEDifferential with Helical Gears	MOTOR TYPE	AC Induction	
BATTERY (QTY/TYPE) 4.2 ELITE - Twin Pack BATTERY CHARGER 811 Watt World Charger KEY OR PEDAL START Pedal DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Differential with Helical Gears	HORSEPOWER (KW)	14.9 HP (11.1 kW)	
BATTERY CHARGER 811 Watt World Charger KEY OR PEDAL START Pedal DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Differential with Helical Gears	ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	
KEY OR PEDAL START Pedal DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Differential with Helical Gears	BATTERY (QTY/TYPE)	4.2 ELITE - Twin Pack	
DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Differential with Helical Gears	BATTERY CHARGER	811 Watt World Charger	
TRANSAXLE Differential with Helical Gears	KEY OR PEDAL START	Pedal	
	DRIVE TRAIN	Motor Shaft Direct Drive	
SPEED CONTROLLER 350 Amp AC Controller	TRANSAXLE	Differential with Helical Gears	
	SPEED CONTROLLER	350 Amp AC Controller	
GEAR SELECTION Dash Mounted Forward-Neutral-Reverse / Key Switch	GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse / Key Switch	
REAR AXLE RATIO 16.99:1	REAR AXLE RATIO	16.99:1	

PERFORMANCE

SEATING CAPACITY	2-Person	
CURB WEIGHT	926 lb (420 kg)	971 lb (440 kg)
BED LOAD CAPACITY	800 lb (363 kg)	500 lb (227 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	900 lb (408 kg)
SPEED	16.5 mph ± .05 mph (26.5 kph ± 0.8 kph)	
TOWING CAPACITY	1500 lb (680 kg) max	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)	

STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)

