## CARRYALL 4X4 SERIES

Club Car

(IR) Ingersoll Rand

## UNSURPASSED DURABILITY, WORRY-FREE PERFORMANCE

You want a vehicle you can depend on, one that won't get stuck in the mud or fall behind. With auto-locking differentials, aircraft-grade frames, and 4-link, semiindependent rear suspension, our 4WD vehicles are ready to handle whatever you throw at them.



CORE-ID L







CARRYALL 1500 MUSCLE MEETS FLEXIBILITY

IntelliTrak™ automatically senses the terrain and shifts power for maximum traction. Combined with a 2000-pound towing capacity and automotive-style rear suspension, the Carryall 1500 can handle any job.



Horsepower

20 hp (gasoline) 20 hp (diesel)

## CARRYALL 1500 Intellitach

#### OUR MOST VERSATILE UTV


The same automatic 4WD system as our Carryall 1500 plus exclusive IntelliTach™ quick-change hydraulic tool attachment system. It's a mini forklift to help you do your best work.



Horsepower 20 hp (diesel)

### CARRYALL 1700 SEATS FOUR AND HAULS CARGO

With automatic four-wheel drive, four seats, and a full-size truck bed, Carryall 1700 can haul more cargo and passengers to places others fear to tread.



1600 lbs

Horsepower 20 hp (gasoline) 20 hp (diesel)

# **READY FOR A** HARD DAY'S WORK

Our new 4x4 Passenger Cab features 40% more airflow and a variety of accessories for comfort, efficiency, and versatility. Carryall AWD UTVs with an added cab help you get a variety of jobs done, even on tough terrain or in extreme weather conditions.




# Intellatach **KEEP YOUR** ESSENTIALS READY

Reduce the need for expensive construction equipment and get a variety of jobs done quickly with our exclusive IntelliTach™ quick-change tool attachment system.





Front Bucket



Plow Blade



Pallet Forks

#### **OPTIONS & ACCESSORIES**

Ask your Club Car sales representative for details.







Strobe Light



Windshield (solid and fold-down available)





High Capacity Updgrade

#### CARRYALL 1500

DIESEI



GASOL INF

ubCa











ENGINE Kawasaki 4-cycle, industrial grade Kubota D722, industrial grade Kubota D722, industrial grade Kawasaki 4-cycle, industrial grade Kubota D722, industrial grade 20.1 hp (15 kW) rated 20 hp (15 kW) rated 20 hp (15 kW) rated 20.1 hp (15 kW) rated 20 hp (15 kW) rated HORSEPOWER @ 3600 RPM per SAE J1995 @ 3600 RPM per SAE J1995 @ 3400 RPM per SAE J1349 @ 3600 RPM per SAE J1995 @ 3400 RPM per SAE J1349 BATTERIES 12-volt 500 CCA 105 min reserve STEERING Rack and ninion with tilt steering Rack and pinion with tilt steering Rack and ninion with tilt steering Rack and pinion with tilt steering Rack and pipion with tilt steering Independent double A-arms with FRONT SUSPENSION coil-over shocks coil-over shocks coil-over shocks coil-over shocks coil-over shocks REAR SUSPENSION Semi-independent 4-link solid axle Semi-independent, 4-link solid axle Semi-independent, 4-link solid axle Semi-independent, 4-link solid axle Semi-independent, 4-link solid axle Twin piston front, single piston rear BRAKES hydraulic disc hydraulic disc hydraulic disc hydraulic disc hydraulic disc PARK BRAKE Mechanical disc Mechanical disc Mechanical disc Mechanical disc Mechanical disc Standard All-terrain, 25 x 11-12, 4-ply TIRES Optional Mud, 25 x 11-12, 6-ply **BED L X W X H** 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) WHEELBASE 82 in (208 cm) 82 in (208 cm) 82 in (208 cm) 114 in (290 cm) 114 in (290 cm) 7.3 in (19 cm) - under differential **GROUND CLEARANCE** 8.2 in (21 cm) 8.2 in (21 cm) 8.2 in (21 cm) 8.2 in (21 cm) 11.1 in (28 cm) - under floorboard FUEL TANK CAPACITY 6.5 gal (24.6 L) CUPB WEIGHT 1430 lb (649 kg) 1550 lb (703 kg) 1751 lb (794 ka) 1630 lb (739 ka) 1750 lb (794 ka) Standard 800 lb (363 kg); Standard 800 lb (363 kg); **BED CAPACITY** Standard 800 lb (363 kg) 800 lb (363 ka) 800 lb (363 ka) With HD Suspension 1050 lb (476 kg) With HD Suspension 1050 lb (476 kg) Standard 1200 lb (544 kg); Standard 1200 lb (544 kg); PAYLOAD CAPACITY Standard 1200 lb (544 kg) 1600 lb (726 ka) 1600 lb (726 ka) With HD Suspension 1450 lb (658 kg) With HD Suspension 1450 lb (658 kg) **TOWING CAPACITY** 2000 lb (907 kg) **OVERALL HEIGHT** 80.3 in (204 cm) 121 in (307 cm) - w/o attachment arm and w/ cylinders stored **OVERALL LENGTH** 124.6 in (317 cm) 124.6 in (317 cm) 136 in (345 cm) - w/ attachment arm 154 in (391 cm) 154 in (391 cm) and cylinder fully extended 155 in (394 cm) - max extended position **OVERALL WIDTH** 58.5 in (149 cm) SPEED RANGE 25 mph (40.2 km/h) 25 mph (40.2 km/h)25 mph (40.2 km/h) 25 mph (40.2 km/h) 25 mph (40.2 km/h) 1 yr/1000 hr limited vehicle warranty LIMITED WARRANTY 2 yr/2000 hr limited powertrain warranty

Dark Gray

Red

Dark Green Colors may vary by product

