

UNMATCHED VERSATILITY. **EXCEPTIONAL** RELIABILITY

The only utility vehicles that can keep up with your customers.

Your renters rely on work vehicles to perform day in and day out, on task after task, with little maintenance, even less attention, and zero headaches. Because we understand that, the Carryall® series by Club Car is designed, developed, and engineered to enable their best work with ease, positioning you—and everyone you serve-for success.

Built to exacting standards with automotive-grade strength, industryleading longevity, and a customizable design, Carryalls are the first and best choice for hardworking teams everywhere.

CARRYALL



- "Our customers demand a
- real workhorse for use in the toughest commercial applications, and the Club Car utility vehicles have proven they are up to the challenge."
- Greg Pasquale, Director of Product Support Synergy Equipment



CARRYALL 1700

POWERFUL HAULING FOR ANY JOB SITE

The industry's only automatic four-wheel drive vehicle has room for up to four people and all their gear.









20 hp (diesel)

1,000 JOBS, ONLY ONE CARRYALL

Things can get rocky out there for your customers. Team members come and go. Budgets fluctuate. Responsibilities (and liabilities) expand. But the Carryall® utility vehicle remains a constant. It keeps on working, hauling cargo, transporting crews, and saving time and money. Now, it's more versatile than ever: by combining leading-edge innovations with the quality you expect, the Carryall is the one utility vehicle that can tackle 1,000 jobs. It stands alone.



CARRYALL 1500

ALL-AROUND HIGH-PERFORMANCE MACHINE

The perfect combination of muscle and flexibility packed on a rustproof, aircraft-grade aluminum frame.



20 hp (gasoline) 20 hp (diesel)





TANK-LIKE DURABILITY, TRUCK-LIKE PERFORMANCE

These vehicles are in it for the long haul.

Carryall® utility vehicles are known for delivering years of trouble-free service. The new vehicles continue that tradition. They retain the core components users prize in the Carryall brand: the rustproof, corrosion-resistant, aircraft-grade aluminum frame and body; tough ArmorFlex™ front body with automotive finish; self-compensating rack-and-pinion steering; independent front suspension system; and unparalleled reliability. But they also incorporate innovative new features and benefits that add even more value.



CARRYALL 300

EASY TO HANDLE

With the tightest turning radius in its class, Carryall 300 delivers unsurpassed maneuverability.



Max Speed 17 mph



Max Vehicle Capacity 800 lbs Horsepower 14 hp (gasoline) 3.3 hp (electric)



CARRYALL 500

JACK OF ALL TRADES

Versatile, rugged, the best choice for those with various tasks.









Max Speed 17 mph Max Vehicle Capacity 1200 lbs Horsepower 14 hp (gasoline) 3.7 hp (electric)



CARRYALL 700

FOR THE LONG HAUL

High hauling capacity with the legendary, rugged Carryall design.



x Speed Max Ve



Max Speed 17 mph Max Vehicle Capacity 1500 lbs Horsepower 14 hp (gasoline) 3.7 hp (electric)



OUTFITTED FOR THE TASK AT HAND

Carryall UTVs are built for hundreds of needs.

No team ever has just one job to do. With the industry's widest range of commercial accessories, including ladder racks, refreshment centers, specialized lighting, and more, we can deliver your rental vehicles equipped with application-specific features designed to improve user productivity.



FACILITIES ENGINEERING

Our facilities engineering Carryall vehicle comes with a van box or duallocking tool box system to help teams stay on the move.



Security continues to evolve, and vehicles have a small profile, tight the Carryall 300 security vehicle is designed to flex with your customers' changing needs. the secure transport of patients.

GROUNDS MAINTENANCE

Club Car's new Carryall 700 grounds maintenance vehicle with hose reel has the reliable power to get the job done on any terrain.



AMBULANCE SERVICES

The Carryall 300 and 1700 ambulance handling, and extra space, allowing for



COMFORTABLE. SAFE PASSENGER TRANSPORT

Built for durable flexibility on campuses, resorts, and more.

Driven by powerful yet quiet gas or zero-emissions electric engines, Club Car Transporter, Transporter XL, and Tempo™ 2+2 vehicles are designed with automotive-grade safety details and packed with comfort and convenience features. They're smart, steady solutions that provide peace of mind for anyone who transports guests.





Tempo 2+2

THE MOST ECONOMICAL PEOPLE MOVER

Boasting the tightest turn radius in the industry, the Tempo 2+2 adds comfort to sporty handling.







800 lbs

Capacity



TRANSPORTER | TRANSPORTER XL

MADE FOR CREWS AND CARGO

Available with a fold-down rear seat to carry up to 300 lbs. and equipped with rustproof aluminum chassis, body, and bed.



17 mph







Capacity

SECURITY

READY FOR ANY TERRAIN

Our IntelliTrak™ all-wheel drive system senses the ground it's on and automatically adjusts between 1- to 4-wheel drive to match the terrain. With no levers, buttons, or training needed, the driver can focus on the job at hand—and trust that the vehicle can cover any ground.

'The Club Cars have proven dependable in the hands of some very demanding rental customers in some of the harshest environments imaginable."

- Greg Pasquale,
Director of Product
Support
Synergy Equipment





Intellitach

EQUIPPED WITH JOB-SPECIFIC ESSENTIALS

Help customers get a variety of jobs done quickly—and reduce the need for expensive construction equipment—with our exclusive IntelliTach™ quick-change tool attachment system.

OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.



Front Bucket



Plow Blade



Pallet Forks



CARRYALL 1700









CARRYALL 1500



CARRYALL 1500§

GASOLINE

| DLINE | |
|-------|--|
| | |
| | |

| ENGINE | Kawasaki 4-cycle, industrial grade | Kubota D722, industrial grade | Kawasaki 4-cycle, industrial grade | Kubota D722, industrial grade | Kubota D722, industrial grade | Kawasaki 4-cycle, industrial grade |
|--------------------|---|---|---|---|---|--|
| HORSEPOWER | 20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349 | 20 hp (15 kW) rated @ 3600 RPM per SAE J1995 | 20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349 | 20 hp (15 kW) rated 3600 RPM per SAE J1995 | 20 hp (15 kW) rated @ 3600 RPM per SAE J1995 | 20.1 hp (15 kW) rated |
| BATTERIES | 12-volt 500 CCA 105 min reserve | 12-volt 500 CCA 105 min reserve | 12-volt 500 CCA 105 min reserve | 12-volt 500 CCA 105 min reserve | 12-volt 500 CCA 105 min reserve | 12-volt 500 CCA 105 min reserve |
| STEERING | Rack and pinion with tilt steering | Rack and pinion with tilt steering | Rack and pinion with tilt steering | Rack and pinion with tilt steering | Rack and pinion with tilt steering | Rack and pinion with tilt steering |
| FRONT SUSPENSION | Independent double A-arms with coil-over shocks | Independent double A-arms with coil-over shocks | Independent double A-arms with coil-over shocks | Independent double A-arms with coil-over shocks | Independent double A-arms with coil-over shocks | Independent double A-arms with coil-over shocks |
| REAR SUSPENSION | Semi-independent, 4-link solid axle | Semi-independent, 4-link solid axle | Semi-independent, 4-link solid axle | Semi-independent, 4-link solid axle | Semi-independent, 4-link solid axle | Semi-independent, 4-link solid axle |
| BRAKES | Twin piston front, single piston rear hydraulic disc | Twin piston front, single piston rear hydraulic disc | Twin piston front, single piston rear hydraulic disc | Twin piston front, single piston rear hydraulic disc | Twin piston front, single piston rear hydraulic disc | Twin piston front, single piston rear hydraulic disc |
| PARK BRAKE | Mechanical disc | Mechanical disc | Mechanical disc | Mechanical disc | Mechanical disc | Mechanical disc |
| TIRES | All-terrain, 25 x 10.5-12, 4-ply | All-terrain, 25 x 10.5-12, 4-ply | All-terrain, 25 x 10.5-12, 4-ply | All-terrain, 25 x 10.5-12, 4-ply | All-terrain, 25 x 10.5-12, 4-ply | All-terrain, 25 x 10.5-12, 4-ply |
| BED LxWxH | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) | 48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm) |
| WHEELBASE | 114 in (290 cm) | 114 in (290 cm) | 82 in (208 cm) | 82 in (208 cm) | 82 in (208 cm) | 82 in (208 cm) |
| GROUND CLEARANCE | 8.2 in (21 cm) | 8.2 in (21 cm) | 8.2 in (21 cm) | 8.2 in (21 cm) | 7.3 in (19 cm) - under differential 11.1 in (28 cm) - under floorboard | 8.2 in (21 cm) |
| FUEL TANK CAPACITY | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) | 6.5 gal (24.6 L) |
| CURB WEIGHT | 1630 lb (739 kg) | 1750 lb (794 kg) | 1430 lb (649 kg) | 1550 lb (703 kg) | 1751 lb (794 kg) | 1387 lb (626 kg) w/o ROPS 1451 lb (658 kg) w/ ROPS |
| BED CAPACITY | 800 lb (363 kg) | 800 lb (363 kg) | Standard 800 lb (363 kg); with HD Suspension 1050 lb (476 kg) | Standard 800 lb (363 kg); with HD Suspension 1050 lb (476 kg) | Standard 800 lb (363 kg) | Standard 800 lb (363 kg); with HD Suspension 1500 lb (680 kg) |
| PAYLOAD CAPACITY | 1600 lb (726 kg) | 1600 lb (726 kg) | With HD Suspension 1450 lb (658 kg) | With HD Suspension 1450 lb (658 kg) | 1200 lb (544 kg) | Standard 1200 lb (544 kg); with HD Suspension 1900 lb (862 kg) |
| TOWING CAPACITY | 2000 lb (907 kg) | 2000 lb (907 kg) | 2000 lb (907 kg) | 2000 lb (907 kg) | 2000 lb (907 kg) | 1300 lb (590 kg) |
| OVERALL HEIGHT | 80.3 in (204 cm) | 80.3 in (204 cm) | 80.3 in (204 cm) | 80.3 in (204 cm) | 80.3 in (204 cm) | 53.4 in (136 cm) w/o ROPS 80.3 in (204 cm) w/ ROPS |
| OVERALLLENGTH | 154 in (391 cm) | 154 in (391 cm) | 1246 in (317 cm) | 124.6 in (317 cm) | 121 in (307 cm) - w/o attachment arm and w/ cylinders stored 136 in (345 cm) - w/ attachment arm and cylinder fully extended 155 in (394 cm) - max extended position | 124.6 in (317 cm) |
| OVERALL WIDTH | 58.5 in (149 cm) | 58.5 in (149 cm) | 58.5 in (149 cm) | 58.5 in (149 cm) | 58.5 in (149 cm) | 58.5 in (149 cm) |
| SPEED RANGE | 25 mph (40.2 km/h) | 25 mph (40.2 km/h) | 25 mph (40.2 km/h) | 25 mph (40.2 km/h) | 25 mph (40.2 km/h) | 19 mph (30 km/h) |
| LIMITED WARRANTY | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain | 1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain |

AWD & 2WD

Club Car

Dark Gray

Colors may vary by product

Dark Green

CARRYALL 300

GASOLINE

Club Car



CARRYALL 500



CARRYALL 700





GASOLINE

ELECTRIC

GASOLINE ELECTRIC

| ENGINE | Kohler EFI, 4-cycle Gas | 48-volt DC | Kohler EFI, 4-cycle Gas | 48-volt DC | Kohler EFI, 4-cycle Gas | 48-volt DC |
|--------------------|--|---|--|---|--|---|
| HORSEPOWER | 14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 | 3.3 hp (2.4 kW) rated, peak 13 hp (9.6 kW) | 14 hp (10.3 kW) rated © 3600 RPM per SAE J1940 | 3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW) | 14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 | 3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW) |
| BATTERIES | 12-volt 500 CCA 105 min reserve | Six 8-volt flooded lead acid | 12-volt 500 CCA 105 min reserve | Eight 6-volt flooded lead acid | 12-volt 500 CCA 105 min reserve | Eight 6-volt flooded lead acid |
| CHARGER | N/A | E.R.I.C. Shelf Charger (650 W high frequency) | N/A | On-board DeltaQ QuiQ (1 kW high frequency) | N/A | On-board DeltaQ QuiQ (1 kW high frequency) |
| STEERING | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion |
| FRONT SUSPENSION | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks |
| BRAKES | Rear-wheel, self-adjusting mechanical drum | Rear-wheel, self-adjusting mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum |
| PARK BRAKE | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock |
| BODY AND FINISH | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish |
| TIRES | 20 x 10-10, 6-ply | 20 x 10-10, 6-ply | 20 x 10-10, 6-ply, premium tread | 20 x 10-10, 6-ply, premium tread | 20 x 10-10, 6-ply, premium tread | 20 x 10-10, 6-ply, premium tread |
| BED LxWxH | 36.2 x 47.5 x 10.5 in (92 x 121 x 27 cm) | 36.2 x 47.5 x 10.5 in (92 x 121 x 27 cm) | 44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm) | 44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm) | 65.5 x 47.5 x 10.5 in (166 x 121 x 27 cm) | 65.5 x 47.5 x 10.5 in (166 x 121 x 27 cm) |
| WHEELBASE | 65.5 in (166 cm) | 65.5 in (166 cm) | 78.1 in (198 cm) | 78.1 in (198 cm) | 99.1 in (252 cm) | 99.1 in (252 cm) |
| GROUND CLEARANCE | 5.2 in (13 cm) | 5.6 in (14 cm) | 5.6 in (14.2 cm) | 5.6 in (14.2 cm) | 5.6 in (14.2 cm) | 5.6 in (14.2 cm) |
| FUEL TANK CAPACITY | 5.5 gal (20.8 L) | N/A | 5.5 gal (20.8 L) | N/A | 5.5 gal (20.8 L) | N/A |
| CURB WEIGHT | 817 lb (371 kg) | 1105 lb (501 kg) | 907 lb (411 kg) | 1393 lb (632 kg) | 993 lb (450 kg) | 1475 lb (669 kg) |
| SPEED RANGE | 15–17 mph (24–27 km/h) | 5–17 mph (8–27 km/h) | 15–17 mph (24–27 km/h) | 5-17 mph (8-27 km/h) | 15–17 mph (24–27 km/h) | 5–17 mph (8–27 km/h) |
| LIMITED WARRANTY | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle |

Dark Gray Dark Green Bright Blue





TRANSPORTER



TRANSPORTER XL



GASOLINE

ELECTRIC

GASOLINE ELECTRIC

GASOLINE

ELECTRIC

| ENGINE | Kohler EFI, 4-cycle Gas | 48-volt DC | Kohler EFI, 4-cycle Gas | 48-volt DC | Kohler EFI, 4-cycle Gas | 48-volt DC |
|--------------------|--|---|--|---|--|---|
| HORSEPOWER | 14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 | 3.3 hp (2.4 kW) rated; peak 13 hp (9.6 kW) | 14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 | 3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW) | 14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 | 3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW) |
| GOVERNOR GUARD | Ground speed | N/A | Ground speed | N/A | Ground speed | N/A |
| BATTERIES | 12-volt 500 CCA 105 min reserve | Six 8-volt flooded lead acid | 12-volt 500 CCA 105 min reserve | Eight 6-volt flooded lead acid | 12-volt 500 CCA 105 min reserve | Eight 6-volt flooded lead acid |
| CHARGER | N/A | E.R.I.C. (650 W high frequency) | N/A | On-board DeltaQ QuiQ (1 kW High Frequency) | N/A | On-board DeltaQ QuiQ (1 kW High Frequency) |
| STEERING | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion |
| FRONTSUSPENSION | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks |
| BRAKES | Rear wheel mechanical drum | Rear wheel mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum |
| PARK BRAKE | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock | Foot operated, multi-lock |
| BODY AND FINISH | Molded-in color, aluminum finish | Molded-in color, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish | ArmorFlex® with automotive paint/clearcoat, aluminum finish |
| TIRES | 18 x 8.50-8, 4-ply rated, premium tread | 18 x 8.50-8, 4-ply rated, premium tread | 20 x 10-10, 6-ply rated, premium tread | 20 x 10-10, 6-ply rated, premium tread | 20 x 10-10, 6-ply rated, premium tread | 20 x 10-10, 6-ply rated, premium tread |
| BED LxWxH | N/A | N/A | 37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box) | 37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box) | N/A | N/A |
| WHEELBASE | 65.5 in (166 cm) | 65.5 in (166 cm) | 99.1 in (252 cm) | 99.1 in (252 cm) | 132.1 in (336 cm) | 132.1 in (336 cm) |
| GROUND CLEARANCE | 4.5 in (11 cm) | 4.5 in (11 cm) | 5.6 in (14 cm) | 5.2 in (14 cm) | 5.6 in (14 cm) | 5.2 in (14 cm) |
| FUEL TANK CAPACITY | 5.5 gal (20.8 L) | N/A | 5.5 gal (20.8 L) | N/A | 5.5 gal (20.8 L) | N/A |
| CURB WEIGHT | N/A | N/A | 932 lb (423 kg) stakeside; 943 lb (428 kg) with rear seat | 1494 lb (678 kg) stakeside; 1505 lbs (684 kg) with rear seat | 1104 lb (501 kg) 8 passenger | 1646 lb (747 kg) 8 passenger |
| SPEED RANGE | 12–15 mph (19.3–24.1 km/h) | 5–15 mph (8–24.1 km/h) | 15–17 mph (24–27 km/h) | 5–17 mph (24–27 km/h) | 15–17 mph (24–27 km/h) | 5–17 mph (24–27 km/h) |
| LIMITED WARRANTY | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle | 3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle | 4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle |

CARRYALL

Talk to your Club Car sales representative to make the most of your rental fleet

LEARN MORE AT CARRYALL.COM



