



Room For So Much More.

The E-Z-GO[®] Valor 6 gives you the space to do so much more. With a distinct combination of durability, functionality, and spacious comfort, it will become more about the ride than the destination. The Valor 6 will keep you going wherever the road takes you - with room to spare.

REAR FACING FLIP SEAT COMFORTABLE SPACE FOR SIX 48-VOLT BATTERY SYSTEM



VALOR[°] 6



Key Features

- 48V AC Powertrain
- Convex Mirror
- Standard LED Taillights
- State of Charge Meter
- Flip-down Rear Facing Seat

Color Options



Platinum



DIMENSIONS

DIMENSIONS	
OVERALL LENGTH	141.5 in (359 cm)
OVERALL WIDTH	45.88 in (117 cm)
OVERALL HEIGHT (W/O CANOPY)	48.38 in (123 cm)
OVERALL HEIGHT (W/ CANOPY)	72.63 in (184 cm)
WHEEL BASE	94 in (239 cm)
FRONT WHEEL TRACK	36.25 in (92 cm)
REAR WHEEL TRACK	36.25 in (92 cm)
GROUND CLEARANCE @ DIFFERENTIAL	5.5 in (14 cm)
POWER	
POWER SOURCE	48 V
MOTOR TYPE	48 Volt AC Induction
HORSEPOWER (KW)	6 hp (4.5 kW)
ELECTRICAL SYSTEM	48V Primary
BATTERIES (QTY/TYPE)	4-12 V Lead Acid Batteries
BATTERY CHARGER	48 V 650 W SC-48 (Delta Q) Charger, 3 m charging cord
KEY OR PEDAL START	Pedal Start
SPEED CONTROLLER	350 Amp
DRIVETRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Dash Mounted FNR/key switch
REAR AXLE RATIO	16.99:1 (Forward)
PERFORMANCE	
PERFORMANCE SEATING CAPACITY	6-Passenger
	6-Passenger 994 lb (452 kg) (without batteries)
SEATING CAPACITY	-
SEATING CAPACITY DRY WEIGHT	994 lb (452 kg) (without batteries)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT	994 lb (452 kg) (without batteries) 1322 lb (601 kg)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND)	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm")
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm")
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in' (18403 cm') 300 lbs. (136 kg)
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm") 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR)	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm") 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in' (18403 cm'') 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES PARKING BRAKE	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in ¹ (18403 cm ⁷) 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum Self-Compensating, Single Point Engagement
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES PARKING BRAKE TIRES	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in ¹ (18403 cm ⁷) 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum Self-Compensating, Single Point Engagement
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES PARKING BRAKE TIRES BODY & CHASSIS	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in* (18403 cm*) 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum Self-Compensating, Single Point Engagement Kenda K500 20x8-10
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES PARKING BRAKE TIRES BODY & CHASSIS FRAME	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm″) 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum Self-Compensating, Single Point Engagement Kenda K500 20x8-10 Welded Steel with DuraShield [™] Powder Coat and E-Coat
SEATING CAPACITY DRY WEIGHT CURB WEIGHT VEHICLE LOAD CAPACITY OUTSIDE CLEARANCE CIRCLE SPEED (LEVEL GROUND) TURNING RADIUS DASH / IP STORAGE CAPACITY LOAD DECK CAPACITY STEERING & SUSPENSION STEERING SUSPENSION (FRONT & REAR) BRAKES PARKING BRAKE TIRES BODY & CHASSIS FRAME BODY & FINISH	994 lb (452 kg) (without batteries) 1322 lb (601 kg) 1200 lb (544 kg) 32.05 ft (9.8 m) 19.5 Mph (31.4 Kph) 16.03 ft (4.9 m) 1123 in° (18403 cm″) 300 lbs. (136 kg) Self-Compensating Reduction Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers Dual rear wheel mechanical self-adjusting drum Self-Compensating, Single Point Engagement Kenda K500 20x8-10 Welded Steel with DuraShield™ Powder Coat and E-Coat Injection Molded TPO

ACCESSORIES AND OPTIONS (WITH EXCEPTIONS OF CANOPY AND WINDSHIELD) WEIGHT MUST BE DEDUCTED FROM LOAD CAPACITY





